

Cpmtools

<http://www.moria.de/~michael/cpmtools/>

GUI → <http://star.gmobbb.jp/koji/cgi/wiki.cgi?page=CpmtoolsGUI>

<https://www.seasip.info/Unix/LibDsk/>

Format description

```

diskdef name                format definition
  seclen n                   128,256,512,1024,.. physical Sector length
  tracks n                   1.. Number of tracks                = (Cylinders *
Sides)
  sectrk n                   1.. Sectors per track
  blocksize n                1024,2048,4096,8192,16384 Block size =
(128*(BLM+1))
  maxdir n                   1.. Number of directory entries    = (DRM+1)
  skew n                     0.. Logical sector skew
  skewtab r1,r2,r3,...      skew table
  boottrk n                  Number of system tracks            = OFS
  offset n | nK | nM | nT    n Byte|n Kilobyte|n Megabyte|n Tracks
  logical extents            Logical extents per physical extent
  os 2.2 | 3 | isx | p2dos | zsys
  libdsk:format name        pcw720,cpcsys, etc. (Optional kann der Typ
mit übergeben werden: format[,type])
end

```

Berechnungen:

```

size := (secLength*sectrk*(tracks-boottrk))/blksiz;
if (extents==0) extents := ((size>=256 ? 8 : 16)*blksiz)/16384; if
(extents==0) extents := 1;
AllocatableDataBlocks := size-(maxdir*32+blksiz-1)/blksiz);

```

posix:

```
physical pos := ((sector+track*sectrk)*secLength)+offset;
```

win32c:

```
SetFilePointer := ((sector+track*sectrk)*secLength)+offset;
```

libdisk:

```
physical sector := track*sectrk + sector + offset/secLength;
```

Viele Hinweise zu libsk, cpmtools, ... und zur Analyse unbekannter Disketten gibt's von Larry Kraemer auf <http://forums.debian.net/viewtopic.php?f=16&t=112244>

Build

Erzeugen mit MINGW/MSYS

```
#-----  
---  
# libdsk  
#-----  
---  
  
tar zxvf libdsk-1.3.3.tar.gz  
cd libdsk-1.3.3  
./configure  
make  
strip *.exe  
make install  
cd ..  
  
#-----  
---  
# cpmtools  
#-----  
---  
  
PDCurses installieren, d:\devtools\MinGW\include\curses.h heißt schon  
richtig?  
  
cd d:\devtools\MinGW\lib\  
copy libpdcurses.a libcurses.a  
  
#-----  
---  
  
tar zxvf cpmtools-2.13.tar.gz  
cd cpmtools-2.13  
./configure --with-diskdefs="" --with-defformat="default" --with-  
libdsk=/local/  
make  
make -i install  
strip /local/bin/*.exe  
  
#-----  
---  
  
tar zxvf cpmtools-2.18.tar.gz  
cd cpmtools-2.18  
  
es gibt Compiler-Probleme mit den mitgelieferten getopt-Daten, deshalb  
- in Makefile.in "getopt$(OBJEXT) getopt1$(OBJEXT) " überall löschen  
- leere Datei getopt_.h anlegen (oder vorhandene leeren)
```

```
./configure --with-diskdefs="" --with-defformat="default" --with-  
libdisk=/local/  
make  
strip *.exe  
make -i install
```

Changes

Changes since 2.20:

- o rc759 diskdef renamed to rc75x, as it works for the series
- o diskdefs.5 added
- o Many disk formats from Larry Kraemer added
- o Renamed ampsdd to ampro400d for consistency with libdisk and because ampsdd very likely was wrong
- o Check for invalid block size
- o Output line number for diskdefs errors

Changes since 2.19:

- o Fixed bug in cpmfs leading to wrongly allocated blocks

Changes since 2.18:

- o More diskdefs entries
- o New diskdefs option to set the libdisk format
- o Fixed various warnings
- o Fixed Makefile if building without curses

Changes since 2.17:

- o Make timestamps in mkfs.com optional and add date stamper creation
- o Better cpm.5 documentation
- o Updated config.guess
- o Fixed error handling for corrupt images or diskdefs
- o Fixed off by one bug in fsck not detecting a wrong block number
- o Fixed too short directory buffer for directory sizes not matching whole blocks

Changes since 2.16:

- o Improved filesystem documentation
- o Many new diskdefs
- o device_win32.c fixed by Bill Buckels

Changes since 2.15:

- * Various small fixes

- * Datestamper support
- * Image offset to access disk slices

libdisk-Formate und Typen

```
d:>dskdump.exe -formats
```

```
Disk formats supported:
```

```
pcw180      : PCW / IBM 180k
pcsys       : CPC System
pcpdata     : CPC Data
pcw720      : PCW / IBM 720k
pcw1440     : PcW16 / IBM 1440k
ibm160      : IBM 160k (CP/M-86 / DOSPLUS)
ibm320      : IBM 320k (CP/M-86 / DOSPLUS)
ibm360      : IBM 360k (CP/M-86 / DOSPLUS)
ibm720      : IBM 720k (144FEAT)
ibm1200     : IBM 1.2M (144FEAT)
ibm1440     : IBM 1.4M (144FEAT)
acorn160    : Acorn 160k
acorn320    : Acorn 320k
acorn640    : Acorn 640k
acorn800    : Acorn 800k
acorn1600   : Acorn 1600k
pcw800      : PCW 800k
pcw200      : PCW 200k
bbc100      : BBC 100k
bbc200      : BBC 200k
mbee400     : Microbee 400k
mgt800      : MGT 800k
trdos640    : TR-DOS 640k
ampro200    : Ampro 40 track single-sided
ampro400d   : Ampro 40 track double-sided
ampro400s   : Ampro 80 track single-sided
ampro800    : Ampro 80 track double-sided
pcw1200     : PcW16 / IBM 1200k
mac400      : Macintosh GCR 400k
mac800      : Macintosh GCR 800k
myz80       : MYZ80 8Mb
pcpm320     : IBM 320k (CP/M-86 / DOSPLUS)
```

```
d:>dskdump.exe -types
```

```
Disk image types supported:
```

```
ntwdm      : NT WDM floppy driver
floppy     : Win32 floppy driver
gotek      : Gotek 1440k disc image collection
gotek72    : Gotek 720k disc image collection
remote     : Remote LibDsk instance
rcpmfs     : Reverse CP/MFS driver
```

```
dsk      : CPCEMU .DSK driver
edsk     : Extended .DSK driver
apridisk : APRIDISK file driver
copyqm   : CopyQM file driver
tele     : TeleDisk file driver
ldbs     : LibDsk block store
sap      : SAP file driver
qrst     : Quick Release Sector Transfer
imd      : IMD file driver
ydisk    : YAZE YDSK driver
raw      : Raw file driver (alternate sides)
rawoo    : Raw file driver (out and out)
rawob    : Raw file driver (out and back)
myz80    : MYZ80 hard drive driver
simh     : SIMH disc image driver
nanowasp : NanoWasp image file driver
logical  : Raw file logical sector order
jv3      : JV3 file driver
dc42     : Disk Copy 4.2
cfi      : CFI file driver
```

From:

<https://hc-ddr.hucki.net/wiki/> - **Homecomputer DDR**

Permanent link:

<https://hc-ddr.hucki.net/wiki/doku.php/cpm/cpmttools?rev=1626352160>

Last update: **2021/07/15 12:29**

